



Material Safety Data Sheet

SECTION 1 - PRODUCT AND COMPANY IDENTIFICATION:

1.1 Product Name: Premium Thin Set

1.2 Company Identification: Southern Grouts and Mortars, Inc.
 1502 SW 2nd Place
 Pompano Beach, Florida 33069
 (954) 943-2288

SECTION 2 - COMPOSITION / INFORMATION ON HAZARDOUS INGREDIENTS

Ingredient:	CAS #:	Occupational Exposure Limit:
1) Portland Cement	65977-15-1	OSHA PEL: 50 MPPCF ACGIH TLV: 10 mg/m3 - TWA

SECTION 3 - PHYSICAL /CHEMICAL PROPERTIES

3.1 Appearance and Odor	3.2 Physical Data
Physical state: Coarse Textured Powder Color: White / Gray or colored Odor: none	Boiling Point: N/A Melting Point: N/A Vapor Pressure: N/A Vapor Density: N/A Evaporation Rate: N/A Solubility in Water: Miscible Specific Gravity: 2.5

SECTION 4 - FIRE AND EXPLOSION DATA

Flash Point: N/A
Flammable Limits: N/A
Extinguishable Media: N/A
Special Fire Fighting Procedures: N/A
Unusual Fire and Explosion Hazards: N/A

SECTION 5 – STABILITY AND REACTIVITY DATA

Stability: Stable
Incompatibility (Materials to avoid): Mineral Acids
Hazardous Decomposition or Byproducts: No appreciable decomposition.
Hazardous Polymerization: N/A

SECTION 6 - HEALTH HAZARD DATA

6.1 Primary Routes of Entry:
Eyes: Yes **Skin:** Yes **Inhalation:** Yes **Ingestion:** No



6.2 Health Hazards

Acute: Portland cement can dry the skin and cause alkali burns. Dust can irritate eyes and upper respiratory systems.

Chronic: Dust can cause inflammation of interior of nose and eyes.

Carcinogenicity: Prolonged exposure to dust over the TLV may cause scarring of lungs and delayed lung injury (Silicosis)

NTP: No **Monographics:** No

Signs and Symptoms of Exposure: Shortness of breath, coughing and redness of eyes.

Medical Conditions Aggravated by Exposure: Hypersensitive individuals may develop allergenic dermatitis.

6.3 Emergency and First Aid Procedure:

Irrigate eyes with water. Wash exposed skin areas with water. Remove person to fresh air. If accidentally ingested consult physician.

SECTION 7 - PRECAUTIONS FOR SAFE HANDLING AND USE

7.1 Handling and Storage:

Protect from moisture

7.2 Other Precautions:

Do not breathe dust and avoid contact with skin and eyes

7.3 Released or Spilled:

Collect spills using dustless method. Wear OSHA approved respirator for Silica dust.

7.4 Waste Disposal Method:

Dispose as common waste according to local, state and Federal Regulations

SECTION 8 – CONTROL MEASURES

Respiratory Protection: OSHA approved respirator for Silica dust.

Ventilation: Yes **Local Exhaust:** Yes **Mechanical:** N/A **Special:** N/A

Protective Gloves: Rubber gloves recommended

Eye Protection: Tight fitting safety goggles

Other Protective Clothing: Barrier cream, boots, and clothing should protect skin from contact with product.

Work Hygienic Practices: Good housekeeping practice is recommended.

Date: 08.2011

Disclaimer:

The information contained herein is based on data considered accurate. However, no warranty is expressed or implied regarding the accuracy. Since the use of this information and the conditions of use of the product are not within the control of Southern Grouts and Mortars, Inc., it is the users obligation and responsibility to determine the condition of safe use of the product. SGM Inc., assumes no responsibility for personal injury or property damage.