

MATERIAL SAFETY DATA SHEET

Reliance Supply Company
1880 N.W. 18th Street
Pompano Beach, FL 33069
Date: 01/01/10
Emergency Telephone: 954-971-9111

Section 1—Product Information

Product Name: Cobble Cure
Description: Solvent Blend
Synonyms: None
Molecular Formula: N/A
Chemical Family:

Section 2—Hazardous Properties

Chemical name(s)	%	TLV	Cas#
Xylenes:	55% to 65%		#215-535-7
2-propdxylethanol	15% to 20%		#2807-30-9
Ethylbenzene	15% to 20%		#100-41-4
Isopropanol	5%		#67-63-0

Section 3—Physical Properties

Color: Clear liquid	Specific Gravity: 875
Appearance: water clear	PH: N/A
Odor: Solvent/alcohol	Boiling Point: 150-300F
Evaporation Rate: 25(ethyl ether=1)	Solubility in Water: NonMiscible

Section 4—Fire and Explosion Data

Flash Point: 56F on lowest component Flammable Limits: Class 1B
Extinguishing Media: Use water fog, foam, CO2 or dry chemical extinguishing media.
Fire Fighting Procedures: Firefighters should be equipped with self-contained breathing apparatus and turn out gear.

Section 5—Health Effects

Routes of entry for solids and liquids include eye and skin contact, ingestion and inhalation. Routes of entry for gases include inhalation and eye contact.
Skin contact may be a route of entry for liquefied gases:

Acute Overexposure Effects:

Material Ingestion may cause gastric upset, pain, diarrhea, lethargy. Inhalation of the vapors may result in respiratory irritation.

Chronic Overexposure Effects:

There are no known chronic effects associated with this material.

First Aid Procedures:

Skin -Wash affected areas with soap and water. Remove and launder contaminated clothing before reuse. If irritation develops, get medical attention.

Eyes: Immediately rinse eyes with running water for 15 minutes. If irritation develops, Get medical attention.

Ingestion: Never give fluids or induce vomiting if victim is unconscious or having convulsions. Get immediate medical attention.

Section 6—Reactivity Data

Stability Data: Stable

Incompatibility: Avoid Oxidants

Conditions/Hazards to Avoid: Maintain storage temperatures at 50-90 F

Hazardous Polymerization: Does not occur.

Corrosive Properties: Not corrosive

Section 7—Personal Protection

Clothing: Gloves, coveralls, apron, and boots as necessary to prevent contact.

Eyes: Chemical goggles, also wear a face shield if splashing occurs.

Respiration: If vapors or mists are generated, wear a NIOSH/MSHA approved (CFR 1910.134) mask if allergies to said product exist.

Section 8—Spill and Leak/ Environmental

Spills should be contained and placed in suitable containers for disposal in a licensed facility. This material is not regulated by RCRA or CERCLA.

Waste Disposal: Incinerate or bury as a solid in a licensed facility. Do not discharge into waterways or sewer systems without proper authority.

Container Disposal: Recommend crushing or other means to prevent unauthorized reuse.

Section 9—Regulatory Information

RCRS Hazardous Waste Number :N/A

DOT Hazard Classification: Flammable

Hazard Rating: Health -2 Reactivity - 0 Special : N/A

The information contained herein is to our knowledge true and accurate. All recommendations and suggestions are made without guarantee, since the conditions of use are beyond our control.

Reliance Supply Company- 1880 NW 18th Street, Pompano Beach FL 33069,