

MATERIAL SAFETY DATA SHEET

Page 1

Reliance Supply Company  
1880 N.W. 18<sup>th</sup> Street  
Pompano Beach, FL 33069  
Date: 01/01/10  
Emergency Telephone: 954-971-9111

Section 1—Product Information

:  
Product Name: Cobble Loc  
Description: Clear Sealer/Coating  
Synonyms: None  
Molecular Formula: N/A  
Chemical Family:

Section 2—Hazardous Properties

Chemical name(s)	%	TLV	Cas#
Part A-Ethers:	5%		#55934-93-5, 1569-01-3
N-Methyl-2Pyrrolidone	<2%		#872-50-4
Part B- Isocyanate			Trade Secret

Section 3—Physical Properties

Color: white liquid	Specific Gravity: 1.1
Appearance: milky	PH: N/A
Odor: mild odor	Boiling Point : 313-355F
Evaporation Rate: 25(ethyl ether=1)	Solubility in Water: Miscible
Freezing Point 30F	

Section 4 –Fire and Explosion Data

Flash Point:220F      Flammable Limits: LEL- N/A      UEL-N/A  
Extinguishing Media: Use water fog, foam, CO2 or dry chemical extinguishing media.  
Fire Fighting Procedures: Firefighters should be equipped with self-contained breathing apparatus and turn out gear.  
Unusual Hazards: There are no known unusual fire or explosion hazards. Vapors are heavier than air.

Section 5—Health Effects

Routes of entry for solids and liquids include eye and skin contact, ingestion and inhalation. Routes of entry for gases include inhalation and eye contact.  
Avoid contact with skin and clothing. May cause respiratory tract irritation with symptoms of coughing, sore throat and runny nose.

Acute Overexposure Effects:

page2

Based on test data and experience with similar products it is believed that this is a low hazard material. Ingestion may cause gastric upset, pain, diarrhea, lethargy. Inhalation of the vapors may result in respiratory irritation. May cause irritation of the skin.

Chronic Overexposure Effects:

Reports have associated repeated and prolonged occupational overexposure to solvents with permanent brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling solvents may be harmful or fatal.

First Aid Procedures:

Skin - Wash affected areas with soap and water. Remove and launder contaminated clothing before reuse. If irritation develops, get medical attention.

Eyes: Immediately rinse eyes with running water for 15 minutes. If irritation develops, Get medical attention.

Ingestion: Never give fluids or induce vomiting if victim is unconscious or having convulsions. Get immediate medical attention.

Section 6—Reactivity Data

Stability Data: Stable

Incompatibility: Avoid Oxidants

Conditions/Hazards to Avoid: Maintain storage temperatures at 50-90 F

Hazardous Polymerization: Does not occur.

Corrosive Properties: Not corrosive

Section 7—Personal Protection

Clothing: Gloves, coveralls, apron, and boots as necessary to prevent contact.

Eyes: Chemical goggles or wear a face shield if splashing occurs.

Respiration: If vapors or mists are generated, wear a NIOSH/MSHA approved (CFR 1910.134) mask if allergies to said product exist.

Section 8—Spill and Leak/ Environmental

Spills should be contained and placed in suitable containers for disposal in a licensed facility. This material is not regulated by RCRA or CERCLA.

Waste Disposal: Incinerate or bury as a solid in a licensed facility. Do not discharge into waterways or sewer systems without proper authority.

Container Disposal: Recommend crushing or other means to prevent unauthorized reuse.

Section 9—Regulatory Information

RCRS Hazardous Waste Number :N/A

DOT Hazard Classification: Not Combustible

Hazard Rating: Health -2    Reactivity - 0    Special: N/A

The information contained herein is to our knowledge true and accurate. All recommendations and suggestions are made without guarantee, since the conditions of use are beyond our control.

Reliance Supply Company- 1880 NW 18<sup>th</sup> Street. Pompano Beach FL 33069,