

MATERIAL SAFETY DATA SHEET

Page 1

Reliance Supply Company
1880 NW 18th Street
Pompano Beach, FL 33069
Date: 6-26-03

Emergency Telephone: 954-971-9111

Section 1 - Product Information

Product name: Non-Skid
Description: Skid Resistant Additive
Synonyms: None
Molecular Formula: N/A
Chemical Family:

Section 2 - Hazardous Ingredients
Chemical Name(s):

8

TLV

Cas#

None

Section 3 - Physical Properties

Color: white Powder
Appearance: fine powder
Odor: None
Evaporation Rate: 25 (ethyl ether=1)

Specific Gravity: .90
PH: N/A
Boiling Point: N/A
Solubility in Water: Non-Miscible

Section 4 - Fire and Explosion Data

Flash Point: >530F
Extinguishing Media: Use water fog, foam, CO2 or dry chemical extinguishing media.

Flammable Limits: LEL-N/A

UEL-N/A

Fire Fighting Procedures: Firefighters should be equipped with self-contained breathing apparatus and turn out gear.

Unusual Hazards: High levels of product dust in the atmosphere may present a dust explosion hazard. No significant health hazard from exposure to product.

Section 5 - Health Effects

Treat Powder as a nuisance dust. Keep dust level below 5mg/m3 for respirable fraction and 10mg/m3 for total dust. OSHA EL 15mg/m3. Exposure may cause dizziness, headache, respiratory irritation or unconsciousness.

Acute Overexposure Effects:

Based on test data and experience with similar products it is believed that this is a low hazard material. Ingestion may cause gastric upset, pain, diarrhea, and lethargy. Inhalation of the vapors may result in respiratory irritation.

Chronic Overexposure Effects:

There are no known chronic effects associated with this material.

First Aid Procedures:

Skin-Wash affected areas with soap and water. Remove and launder contaminated clothing before reuse. If irritation develops, get medical attention.
Eyes-Immediately rinse eyes with running water for 15 minutes. If irritation develops, get medical attention.
Ingestion- Never give fluids or induce vomiting if the victim is unconscious or having convulsions. Get immediate medical attention.
Inhalation- Move to fresh air. Aid in breathing, if necessary, and get immediate medical attention.

Section 6 - Reactivity Data

Stability Data: Stable
Incompatibility: Avoid Oxidants
Conditions/Hazards to Avoid: Maintain storage temperature at 50-90F.
Hazardous Polymerization: Does not occur.
Corrosive Properties: Not corrosive.

Section 7 - Personal Protection

Clothing: Any clothing that can prevent contact with skin.
Eyes: Chemical goggles
Respiration: If vapors or mists are generated, wear a NIOSH/MSHA approved (CFR 1910.134) mask if allergies to said product exist.
Ventilation: Open all doors windows to allow for adequate air flow and circulation.

Section 8 - Spill and leak/ environmental

Spills should be contained and placed in suitable containers for disposal in a licensed facility. This material is not regulated by RCRA or CERCLA.
Waste Disposal: Incinerate or bury as a solid in a licensed facility. Do not discharge into waterways or sewer systems without proper authority.
Container Disposal: Recommend crushing or other means to prevent unauthorized reuse.

Section 9 - Regulatory Information

RCRA Hazardous Waste Number: N/A
DOT Hazard Classification: Flammable
Hazard Ratings: Health-1 Fire-1 Reactivity-0 Special: NA

The information contained herein is to our knowledge true and accurate. All recommendations and suggestions are made without guarantee, since the conditions of use are beyond our control.